

COURAGIA M/T Dimension Data

SER	Size	PR	LI/SS	Overall		Diameter		Section Width		Standard Rim	Approved Rim	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		Sidewall
				mm	in	mm	in	mm	in	in	Width	mm	in	in32"	mm	Kg	Cold	KGS	LBS	Type
75	LT 235/75R15	6	104/101Q	734	28.6	228	8.9	6.5	6-7	168	6.6	19	15	15.5	50	900/825	1985/1820	OWL		
	⊙ LT 265/75R16	8	119/116Q	807	31.5	260	10.1	7.5	7-8	193	7.5	19	15	20.4	65	1360/1250	3000/2755	OWL		
	⊙ ▼ LT 285/75R16	8	122/119Q	835	32.6	281	11.0	8.0	7.5-8.5	208	8.1	19	15	N/A	65	1500/1360	3305/3000	OWL		
80	▼ LT30*9.50R15	6	104Q	757	29.5	252	9.8	7.5	7-8	192	7.5	19	15	17.3	50	900	1985	OWL		
	LT31*10.5R15	6	109R	785	30.6	268	10.5	8.5	7-9	200	7.8	19	15	19.1	50	1030	2270	OWL		
	▼ LT33*12.50R15	6	108Q	833	32.5	325	12.7	10.0	9.5-10.5	248	9.7	19	15	21.9	35	1000	2205	OWL		
	▼ 205/80R16C	8	110/108Q	734	28.6	210	8.2	6.0	5.5-6.5	160	6.2	19	15	15.4	65	1060/1000	2337/2205	OWL		
	▼ LT33*13.50R15	6	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OWL		
85	⊙ LT 235/85R16	10	120/116Q	806	31.4	231	9.0	6.5	6-7	170	6.6	19	15	19.5	80	1400/1260	3086/2778	OBL		

Above data subject to change without notice.

▼ Currently under development.

⊙ Sidewall : 3 Polyester.