

SER	SIZE	P,R	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		Sidewall
				mm	in	mm	in	in	Width (in)	mm	in	in32"	mm			Kg	Cold	
70	LT255/70R16	6PR/C	108/104Q	770	30.3	254	10.0	7.5	7.5	216	8.5	12	9.8	17.0	53	1000/ 900	2200/ 1980	OWL
75	P 235/75R15	-	105S	734	28.9	235	9.3	6.5	6.5	165	6.5	11	9.1	13.8	36	925	2035	OWL
	LT 235/75R15	6PR/C	104/101Q	735	28.9	228	9.0	6.5	6.5	169	6.7	14	11.1	15.9	53	900/ 825	1980/ 1815	OWL
	LT 215/75R15	6PR/C	100/97Q	705	27.8	209	8.2	6.0	6	155	6.1	13	10.6	13.0	53	800/730	1760/1606	OWL
	LT 225/75R16	8PR/D	110/107P	746	29.4	216	8.5	6.0	6	166	6.5	14	11.1	16.1	68	1060/ 975	2332/ 2145	OWL
	LT265/75R16	6PR/C	123/120N	805	31.7	258	10.2	6.5	6-7	184	7.2	14	11.6	21.5	80	1550/1400	3417 / 3086	OWL
80	LT 30*9.50R15	6PR/C	104R	756	29.8	252	9.9	7.5	7.5	192	7.6	16	12.8	18.3	53	900	1980	OWL
	LT 31*10.50R15	6PR/C	109R	782	30.8	272	10.7	8.5	8.5	201	7.9	16	12.8	20.0	53	1030	2266	OWL
	195/80R15	-	94S	688	27.1	193	7.6	5.0	5	185	7.3	11	8.7	10.8	36	670	1474	OWL
	205/80R16	-	104S RF.	733	28.9	205	8.1	5.5	5.5	152	6.0	11	8.4	12.8	65	900	1980	OWL
85	LT235/85R16	10PR/E	120/116N	807	31.8	228	9.0	6.5	6.5	172	6.8	15	12.0	19.1	53	1400/ 1250	3080/ 2750	OWL

MS351A/T Dimension Data

Above data subject to change without notice.
▼ Currently under development.