

SER	SIZE	P.R	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim	Tread Width		Tread Depth		Weight	Standard PSI	Max Load		UTQG	Sidewall
				mm	in	mm	in			in	Width (in)	mm	in			in32"	mm		
65	205/65R15C	6	102/100T	647	25.5	205	8.1	6.0	5~7	156	6.1	12	9.5	10.5	65	850/800	1870/1760	-	
	215/65R15C	6	104/102T	662	26.1	215	8.5	6.5	6~7	166	6.5	12	9.5	13.1	65	900/850	1980/1870	-	
	P215/65R16	-	98T	690	27.2	212	8.3	6.5	6~7	158	6.2	10	7.9	12.2	36	710	1562	300BB	OBL
70	205/70R15	-	95S	670	26.4	205	8.1	5.5	5~6.5	146	5.7	11	8.7	15.7	36	690	1518	220BB	
	225/70R15C	8	112/110R	697	27.4	228	9.0	6.5	6~7	168	6.6	12	9.5	13.0	65	1120/1060	2464/2332	-	
	P235/70R16	-	106S	736	29.0	234	9.2	7.0	6.5~7.5	184	7.2	12	9.5	15.7	36	900	1980	300BB	OWL
	P265/70R16	-	112S	778	30.6	267	10.5	8.0	7.5~8.5	204	8.0	12	9.5	19.2	36	1090	2398	300BB	OWL
75	205/75R16C	8	110/108R	715	28.1	205	8.1	5.5	5~6	140	5.5	12	9.5	12.1	65	1060/1000	2332/2200	-	
	LT245/75R16	10PR/E	120/116N	775	30.5	245	9.6	7.0	6.5~7.5	164	6.5	14	11.1	16.9	80	1400	3080	-	OWL
	P245/75R16	-	109S	775	30.5	245	9.6	7.0	6.5~7.5	170	6.7	11	8.7	18.5	36	1030	2266	300BB	OWL
	P265/75R16	-	114S	805	31.7	265	10.4	7.5	7~8	204	8.0	11	9.6	18.6	36	1180	2596	300BB	OWL
80	P215/80R15	-	102S	722	28.4	215	8.5	6.0	5.5~6.5	160	6.3	12	9.5	18.1	36	850	1870	300BB	OWL
	LT31*10.50R15	6PR/C	109R	782	30.8	272	10.7	0.0	8~9	210	8.3	16	12.6	19.0	50	1030	2266	-	OWL

MS357H/T Dimension Data

Above data subject to change without notice.