

SS535 Dimension Data

SER	SIZE	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG
			mm	in	mm	in			in	Width (in)	mm	in			in32"	mm	
50	195/50R15	82V	575	22.6	195	7.7	5.5	4.5-6.5	176	6.9	9	7.4	8.6	36	475	1045	260AA
	205/50R15	86V	585	23.0	205	8.1	5.5	4.5-6.5	184	7.2	9	7.5	9.0	36	530	1166	260AA
	195/50R16	84V	600	23.6	195	7.7	5.5	4.5-6.5	176	6.9	9	7.4	9.1	36	500	1100	260AA
	205/50R16	87V	585	24.0	205	8.1	5.5	4.5-6.5	184	7.2	10	7.7	10.9	36	545	1199	260AA
	225/50R16	92V	630	24.8	225	8.9	6.0	4-7	206	8.1	10	7.7	11.4	36	630	1386	260AA
55	195/55R15	85V	593	23.3	195	7.7	5.5	4.5-6.5	166	6.9	9	7.4	8.7	36	500	1100	260AA
	205/55R15	88V	652	23.8	205	8.1	5.5	4.5-6.5	184	7.2	9	7.5	9.0	36	560	1232	260AA
	205/55R16	91V	630	24.8	205	8.1	6.5	5.5-7	184	7.2	10	7.7	10.5	36	615	1353	260AA
	225/55R16	95V	652	25.7	225	8.9	6.0	5-7	196	7.7	10	8.1	11.5	36	690	1518	260AA
60	185/60R13	80H	552	21.7	183	7.2	5.0	4-6	148	5.8	10	8.1	7.3	36	450	990	320AA
	185/60R14	82V	578	22.8	183	7.2	5.0	4-6	148	5.8	10	8.2	8.0	36	475	1045	320AA
	195/60R14	86V	590	23.2	195	7.7	5.5	4.5-6.5	158	6.2	10	8.3	8.7	36	530	1166	320AA
	195/60R15	88V	615	24.2	195	7.7	5.5	4.5-6.5	158	6.2	10	8.3	9.3	36	560	1232	320AA
	205/60R15	91V	627	24.7	205	8.1	5.5	4.5-6.5	168	6.6	11	8.4	9.7	36	615	1353	320AA
65	185/65R14	86V	596	23.5	185	7.3	5.0	4-6	144	5.7	10	8.2	8.2	36	530	1166	320AA
	195/65R15	91V	635	25.0	195	7.7	6.0	5-7	156	6.1	10	8.3	9.8	36	615	1353	320AA
	205/65R15	94V	647	25.5	205	8.1	5.5	4.5-6.5	164	6.5	11	8.4	10.1	36	670	1474	320AA

Above data subject to change without notice.